



NOTE:

1. TRANSVERSE BARS MAY BE OMITTED WHEN CONCRETE FOR RIBBON CURB IS PLACED WITH A SELF-PROPELLED CURB MACHINE THAT PROVIDES CORRECT PLACEMENT OF THE LONGITUDINAL BARS.
2. RIBBON CURB SHALL BE PLACED AND/OR REPLACED IN ACCORDANCE WITH [ST-20B](#) UNLESS OTHER DETAILS ARE SHOWN IN THE PLANS AND APPROVED BY THE CITY.

RIBBON CURB DETAIL
(NO SCALE)



ENGINEERING DIVISION

DISCLAIMER: THE USE OF THIS STANDARD IS GOVERNED BY THE "TEXAS ENGINEERING PRACTICE ACT". NO WARRANTY OF ANY KIND IS MADE BY THE CITY OF WACO FOR ANY PURPOSE WHATSOEVER. THE CITY OF WACO ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS STANDARD TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES RESULTING FROM ITS USE.

REVISIONS			
NO.	COMMENTS	BY	DATE
1	ADD NOTE 2	MZ	11/15/2024
##	DESCRIPTION	FL	MM/DD/YYYY

DATE	01/01/2024
ST-16	